

PRODUCT	LV-7385	LV-7380	LV-7285	LV-7280
ITEM CODE	4324B002	4325B002	4326B002	4327B002
UPC CODE	013803120868	013803120875	013803120882	013803120899



### Suggested List Price:

LV-7385: \$1,699.00 LV-7380: \$999.00 LV-7285: \$899.00 LV-7280: \$799.00

### FEATURES

- **Native XGA Resolution (1024x768)** - Display widescreen laptops & monitors
- **High Brightness** - Bright, sharp images
  - LV-7385: 3500 Lumens
  - LV-7380: 3000 Lumens
  - LV-7285: 2600 Lumens
  - LV-7280: 2200 Lumens
- **1.2x Zoom Lens** - Faithfully projects images, offering ease of placement
- **DVI-I Interface (HDCP Compliant)** - Output high quality digital images & video
- **Improved Lamp Lighting System** - Operates lamp at lower wattage
- **Lower Power Consumption** - Stand-by power consumption now less than 1W
- **Carbon Reduction Meter** - Displays CO2 reduction when in Quiet Mode
- **Auto Energy Saver** - Quiet Mode activated when no input signal detected
- **Quick Power-Off** - No cool down period required
- **Long Lamp Life** - Up to 5,000 hours in Quiet Mode
- **Computer Sync** - Projector automatically turns on and syncs with your computer when an input signal is detected
- **Closed Captioning** - Display closed captioning information
- **Whiteboard Mode** - Reduces the reflective bright spots projected on a whiteboard
- **7-Watt Speakers** - Clearly hear audio in large rooms
- **Network Connectivity** - Built in RJ-45 port for easy remote management
- **Easy Access Lamp** - Easily replace the lamp on ceiling installed projectors
- **Quiet Operation** - As low as 29 dB
- **Warranty** - 3 Year Parts and Labor / 120 Day on Lamp
- **Canon's Triple P (Projector Protection Program)** - A service program that provides a loaner projector of equal or greater quality to the end user in the event their projector needs to be repaired\*

\* Based on availability, for complete details contact your Canon sales representative

### CONTENTS OF KIT

- Projector
- Power Cable
- VGA-VGA Computer Cable
- DVI-VGA Adapter
- Lens Cap
- Remote Control (with 2 AAA batteries)
- Soft Carrying Case
- Manual / Start Guide / Warranty Card

### OPTIONAL ACCESSORIES

ITEM CODE NO.	DESCRIPTION	SUGGESTED LIST PRICE
3522B003	LV-LP31 REPLACEMENT LAMP (LV-7385)	449.00
4330B001	LV-LP32 REPLACEMENT LAMP (All Others)	449.00
3523B001	LV-CL15 CEILING MOUNT	549.00
7502B001	LV-CA29 DVI-D CABLE	69.00
9270B001	LV-CA32 COMPONENT CABLE	60.00

### PACKAGING INFORMATION

PROJECTOR	W x D x H	WEIGHT
LV-7385 / LV-7380	16.20 x 17.40 x 10.0 in	12.95 lbs
LV-7275 / LV-7280	(411.48 x 441.96 x 254 mm)	(5.87 kg)

### SPECIFICATIONS

BASIC	IMAGING DEVICE	0.63" Transmissive LCD Panels x 3 (w/ MLA)		
	ASPECT RATIO	4:3		
	NATIVE RESOLUTION	XGA (1024 x 768)		
	BRIGHTNESS	LV-7385: 3500 Lumens LV-7380: 3000 Lumens LV-7285: 2600 Lumens LV-7280: 2200 Lumens		
	UNIFORMITY	85%		
	CONTRAST	LV-7385 / LV-7380: 500:1 LV-7285 / LV-7280: 500:1 or 2000:1 (with Auto Iris)		
OPTICS	VERTICAL KEYSTONE	+/- 30 degrees (Auto/Manual)		
	PROJECTION LENS	F1.7 - 2.0, f=19.8 - 23.7mm		
	LENS OFFSET	8.4 : 1.6		
	ZOOM	1.2x Zoom (Manual)		
	FOCUS	Manual		
	SCREEN SIZE	21" - 300"		
IMAGE ADJUSTMENTS	PROJECTION DISTANCE COVERAGE	2.6 - 37.1 ft		
	THROW RATIO	1.53 - 1.84:1		
	IMAGE MODE	sRGB, Presentation, Standard, Cinema, Video		
	CLOSED-CAPTIONING	Yes		
	COLOR ADJUST	RGB Manual		
	WALL CORRECTION	Auto		
INPUT SIGNALS	SCREEN COLOR CORRECTION	Whiteboard / Greenboard / Greenboard (gray) / Light Yellow / Light Green / Light Blue / Sky Blue / Light Rose / Pink		
	MOUNTING	None / Ceiling Mounted / Rear / Rear Ceiling Mounted		
	TILT ANGLE	Adjusting foot up to 10 degrees		
	DIGITAL PC INPUT	SXGA+ / SXGA / WXGA / XGA / SVGA / VGA / MAC		
	SCANNING FREQUENCY	H:15-100 kHz, V:50-120 Hz		
	ANALOG PC INPUT	UXGA / SXGA+ / SXGA / WXGA / XGA / SVGA / VGA / MAC		
TERMINALS	SCANNING FREQUENCY	H:15-100 kHz, V:50-120 Hz		
	DOT CLOCK	108MHz or less		
	VIDEO INPUT / S-VIDEO INPUT	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N / PAL-60		
	COMPONENT INPUT	1080i / 720p / 576p / 576i / 480p / 480i		
	INPUT	DVI-I 29PIN	Digital PC input (HDCP Compliant) / Analog (RGB) PC input	
		D-SUB 15PIN	Analog PC input / Component input	
RCA		Composite Video input		
RCA		Stereo Audio input (L/R)		
MINI DIN 4 PIN		S-Video input		
MINI-JACK		Stereo Audio input x 2		
OUTPUT	D-SUB 15PIN	Analog PC output		
	MINI-JACK	Stereo Audio output		
CONTROL	RS-232	D-sub 9pin		
	RJ-45	Yes		
LAMP	BUILT-IN SPEAKER	7W (Mono)		
	TYPE	LV-7385: 230W NSH (AC) LV-7380/LV-7285/LV-7280: 180W NSH (AC)		
	POWER (NORMAL/QUIET)	LV-7385: 230W / 170W LV-7360/LV-7285/LV-7280: 180W / 145W		
	LAMP LIFE (NORMAL/QUIET)	4000 / 5000 Hours		
	QUICK LAMP REPLACEMENT	Top Panel		
REMOTE CONTROL	SENSOR	Wireless Infrared, Front		
RATINGS	FAN NOISE (NORMAL/QUIET)	35 / 29 dB		
	POWER	CONSUMPTION (NORMAL/QUIET/STANDBY)	LV-7385: 294W / 228W / 0.7W LV-7380/LV-7285/LV-7280: 239W / 196W / 0.7W	
		VOLTAGE	AC100 to 240V, 50/60Hz	
	TEMPERATURE	OPERATING	41° to 104° F (5° to 40° C)	
		STORAGE	14° to 122° F (-10° to 50° C), 20%RH - 80%RH	
	DIMENSIONS (W x D x H)	12.48 x 13.23 x 4.37 in / (317 x 336 x 111mm)		
WEIGHT	7.28 lbs (3.3 kg)			

All prices, specifications, and availabilities subject to change without prior notice.