

<b>PRODUCT</b>	<b>LV-8310</b>	<b>LV-8215</b>
<b>ITEM CODE</b>	<b>4328B002</b>	<b>4329B002</b>
<b>UPC CODE</b>	<b>013803120905</b>	<b>013803120912</b>



### Suggested List Price:

**LV-8310:** \$1,199.00    **LV-8215:** \$1,099.00

### FEATURES

- **Native WXGA Resolution (1280x800)** - Display widescreen laptops & monitors
- **High Brightness** - Bright, sharp images
  - LV-8310: 3000 Lumens
  - LV-8215: 2600 Lumens
- **1.2x Zoom Lens** - Faithfully projects images, offering ease of placement
- **DVI-I Interface (HDCP Compliant)** - Output high quality digital images & video
- **Improved Lamp Lighting System** - Operates lamp at lower wattage
- **Lower Power Consumption** - Stand-by power consumption now less than 1W
- **Carbon Reduction Meter** - Displays CO2 reduction when in Quiet Mode
- **Auto Energy Saver** - Quiet Mode activated when no input signal detected
- **Quick Power-Off** - No cool down period required
- **Long Lamp Life** - Up to 5,000 hours in Quiet Mode
- **Computer Sync** - Projector automatically turns on and syncs with your computer when an input signal is detected
- **Closed Captioning** - Display closed captioning information
- **Whiteboard Mode** - Reduces the reflective bright spots projected on a whiteboard
- **7-Watt Speakers** - Clearly hear audio in large rooms
- **Network Connectivity** - Built in RJ-45 port for easy remote management
- **Easy Access Lamp** - Easily replace the lamp on ceiling installed projectors
- **Quiet Operation** - As low as 29 dB
- **Warranty** - 3 Year Parts and Labor / 120 Day on Lamp
- **Canon's Triple P (Projector Protection Program)** - A service program that provides a loaner projector of equal or greater quality to the end user in the event their projector needs to be repaired\*

\* Based on availability, for complete details contact your Canon sales representative

### CONTENTS OF KIT

- Projector
- Power Cable
- VGA-VGA Computer Cable
- DVI-VGA Adapter
- Lens Cap
- Remote Control (with 2 AAA batteries)
- Soft Carrying Case
- Manual / Start Guide / Warranty Card

### OPTIONAL ACCESSORIES

ITEM CODE NO.	DESCRIPTION	SUGGESTED LIST PRICE
3522B003	LV-LP31 REPLACEMENT LAMP	449.00
3523B001	LV-CL15 CEILING MOUNT	549.00
7502B001	LV-CA29 DVI-D CABLE	69.00
9270B001	LV-CA32 COMPONENT CABLE	60.00

### PACKAGING INFORMATION

PROJECTOR	W x D x H	WEIGHT
LV-8310 / LV-8215	16.20 x 17.40 x 10.0 in (411.48 x 441.96 x 254 mm)	12.95 lbs (5.87 kg)

### SPECIFICATIONS

BASIC	IMAGING DEVICE		0.59" Transmissive LCD Panels x 3 (w/ MLA)
	ASPECT RATIO		16:10
	NATIVE RESOLUTION		WXGA (1280 x 800)
	BRIGHTNESS		LV-8310: 3000 Lumens LV-8215: 2600 Lumens
	UNIFORMITY		85%
	CONTRAST		LV-8310: 500:1 Contrast Ratio LV-8215: 450:1 Contrast Ratio
	VERTICAL KEYSTONE		+/- 30 degrees (Auto/Manual)
OPTICS	PROJECTION LENS		F1.7 - 2.0, f=19.8 - 23.7mm
	LENS OFFSET		9.1 : 0.9
	ZOOM		1.2x Zoom (Manual)
	FOCUS		Manual
	SCREEN SIZE		21" - 300"
	PROJECTION DISTANCE COVERAGE		2.6 - 39.4 ft
	THROW RATIO		1.62 - 1.95:1
IMAGE ADJUSTMENTS	IMAGE MODE		sRGB, Presentation, Standard, Cinema, Video
	CLOSED-CAPTIONING		Yes
	COLOR ADJUST		RGB Manual
	WALL CORRECTION		Auto
	SCREEN COLOR CORRECTION		Whiteboard / Greenboard / Greenboard (gray) Light Yellow / Light Green / Light Blue / Sky Blue / Light Rose / Pink
	MOUNTING		None / Ceiling Mounted / Rear Rear Ceiling Mounted
	TILT ANGLE		Adjusting foot up to 10 degrees
INPUT SIGNALS	DIGITAL PC INPUT		SXGA+ / SXGA / WXGA / XGA / SVGA / VGA / MAC
	SCANNING FREQUENCY		H:15-100 kHz, V:50-120 Hz
	ANALOG PC INPUT		UXGA / SXGA+ / SXGA / WXGA / XGA / SVGA / VGA / MAC
	SCANNING FREQUENCY		H:15-100 kHz, V:50-120 Hz
	DOT CLOCK		108MHz or less
	VIDEO INPUT / S-VIDEO INPUT		NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N / PAL-60
	COMPONENT INPUT		1080i / 720p / 576p / 576i / 480p / 480i
TERMINALS	INPUT	DVI-I 29PIN	Digital PC input (HDCP Compliant) / Analog (RGB) PC input
		D-SUB 15PIN	Analog PC input / Component input
		RCA	Composite Video input
		RCA	Stereo Audio input (L/R)
		MINI DIN 4 PIN	S-Video input
	OUTPUT	MINI-JACK	Stereo Audio input x 2
		D-SUB 15PIN	Analog PC output
	CONTROL	RS-232	D-sub 9pin
		RJ-45	Yes
	BUILT-IN SPEAKER		7W (Mono)
LAMP	TYPE		230W NSH (AC)
	POWER (NORMAL/QUIET)		230 / 170 W
	LAMP LIFE (NORMAL/QUIET)		4000 / 5000 Hours
	QUICK LAMP REPLACEMENT		Top Panel
REMOTE CONTROL	SENSOR		Wireless Infrared, Front
RATINGS	FAN NOISE (NORMAL/QUIET)		35 / 29 dB
	POWER	CONSUMPTION (NORMAL, QUIET, STANDBY)	294W / 228W / 0.7W
		VOLTAGE	AC100 to 240V, 50/60Hz
	TEMPERATURE	OPERATING	41° to 104° F (5° to 40° C)
		STORAGE	14° to 122° F (-10° to 50° C), 20%RH - 80%RH
	DIMENSIONS (W x D x H)		12.48 x 13.23 x 4.37 in (317 x 336 x 111 mm)
WEIGHT		7.28 lbs (3.3 kg)	

All prices, specifications, and availabilities subject to change without prior notice.